PROJECT NAME:	DATE:	TYPE:
SPECIFIER:	PREPARED BY:	
PART NO.:		

LED CLOSET LIGHT SERIES

TBD.CL45

LED CUSTOM CLOSET STORAGE LIGHT



This selection of the LED Closet Light Series is custom designed for use in residential and commercial closets, including closet storage areas with clothing. Suitable for undercabinet, valence, millwork, recessed and surface mount applications. This custom version is offered with a 45 degree channel, and can be sized in 2” increments up to 98”. Available in either standard 3.0W, or high output 4.4W. Fully Dimmable.

FEATURES

- 24V DC
- 3.0W Standard or 4.4W High Output Per Ft.
- 36 LED’s Per Ft.
- 240 Lm/Ft Standard or 355 Lm/Ft High Output
- 90 or 95 CRI
- Linked up to 24’ Standard, or 30‘ High Output
- Custom Lengths - 2” Increments - up to 98”
  98” Only - Additional fee for Black (Powder Coat)
- Requires Remote TLS Power Supply:
  Dimmable and Non-Dimmable options available
- Certifications: UL Listed and NEC / Approved for closet and closet storage areas
- Long Life 50,000 Hours
- Eco-friendly, No IR, No UV, will not degrade fabric or artwork
- Frosted lens eliminates LED dots
- Versatile mounting clips allow for angled installation
- Snap-on inline motion sensor for easy installation (optional)
- Door Jam Switch (optional)

OUTPUT OPTIONS

STRIP	WATTS	LEDS/FT	LUMENS/FT	RATING
STANDARD	3.0	36	240	INDOOR
HIGH OUTPUT	4.4	36	355	INDOOR

Certification - NRTL Listed. Suitable for installation in storage areas with clothing in accordance with NEC Article 410.2 & 410.16 and CEC section 30-204 in clothes closet. Must be assembled as a fixture at manufacturer facility to be compliant.

INDOOR · DIMMABLE · 90+ CRI

ORDERING GUIDE

TBD.CL45 — [CC] — [ ] — [ ] — [ ] — [ ]

LENGTH
CC - Custom
Lengths available in 2” increments from 6” to 98”

FINISH
SI - Silver
BK - Black

LENS
C - Clear
F - Frosted

POWER FEED
EF - End Feed
BF - Bottom Feed
L - Left Side Feed
R - Right Side Feed

CONNECTORS
H - 60” Hardwire
HH - 60” Hardwire at each end
HD - 60” Hardwire one end + DC connector on male end
D - DC Connector (female end)
DD - DC connector at each end (female + male end)

OUTPUT OPTIONS

[ ] — [ ] — [ ]

OUTPUT
S - Standard 3.0W
HO - High Output 4.4W

TEMP / COLOR
30K - 3000K
40K - 4000K

CRI
90 - 90 CRI
95 - 95 CRI

TBD LED SOLUTIONS
218 E Valley Rd, Ste 104 – PMB377, Carbondale, CO 81623
www.tbdledsolutions.com

PROJECT NAME:	DATE:	TYPE:
SPECIFIER:	PREPARED BY:	
PART NO.:		

LED CLOSET LIGHT SERIES

TBD.CL45

LED CUSTOM CLOSET STORAGE LIGHT

ACCESSORIES

TBD.CL45 ACCESSORIES

Link Ext. Cable
TBD.CL-LNKDC-40
TBD.CL-LNKDC-120
TBD.CL-LNKDC-144
TBD.CL-LNKDC-240

Hardwire Cable
TBD.CL-HWDC-8
TBD.CL-HWDC-24
TBD.CL-HWDC-60
TBD.CL-HWDC-120

TBD.SWITCH200
Door Jam Switch (Optional)

TBD.IN-LINE/SWITCH
Inline Switch

TBD.IN-LINE/DIM
Inline Dimmer

*Compatible with any TBD hardwire or plug-in drivers, 12V or 24V

Maximum Load:
12V - 24 Watts
24V - 48 Watts

TBD.45-EC
End Caps
(2 Included)

TBD.45-MC
Mounting Clips
(2 Included)