

PROJECT NAME:	DATE:	TYPE:
SPECIFIER:	PREPARED BY:	
PART NO.:		



LED POWER SUPPLIES

TBD.PSDM

LED MAGNETIC DIMMABLE DRIVERS - CLASS 2



TBD.PSDM is generally used for DC LED systems and is compatible with low voltage magnetic dimmer switches (MLV TRIAC dimmer). Magnetic drivers are available in a range of wattages and are offered in 12V and 24 V DC output. These dimmable drivers are suitable for dry or wet locations (NEMA 3 enclosure) and are equipped with primary and secondary protection circuit breakers.

FEATURES

- 12V and 24V DC
- Class 2
- Dimmable
- Suitable for Indoor/Outdoor Use IP65
- NEMA 3R – Outdoor Use
- Two Knock-outs, one on each side
- Auto-Reset Feature
- Larger wattage options available upon request.
- Per UL Code for Magnetic Transformers, install in upright position only.

TBD.PSDM-20W-12
5.6 in. x 2 in. x 2.14 in.

TBD.PSDM-20W-24
5.6 in. x 2 in. x 2.14 in.

TBD.PSDM-40W-12
5.6 in. x 2 in. x 2.14 in.

TBD.PSDM-40W-24
5.6 in. x 2 in. x 2.14 in.

TBD.PSDM-60W-12
6.55 in. x 2.25 in. x 2.55 in.

TBD.PSDM-60W-24
6.55 in. x 2.25 in. x 2.55 in.

TBD.PSDM-100W-24
6.55 in. x 2.25 in. x 2.55 in.



ORDERING GUIDE

TBD.PSDM — —

WATTAGE

- 20W** - 20 Watt Max
- 40W** - 40 Watt Max
- 60W** - 60 Watt Max
- *100W** - 96 Watt Max

VOLTAGE

- 12** - 12V DC
- 24** - 24V DC

***NOTE:** 100W only available in 24V